



FOGGING SYSTEMS COVERS 4000m³

OT-U4000PP / Up to 4000m³ in 180seconds.



SPECIFICATIONS

MODEL NO.	OT-U4000PP	
GENERAL SPECIFICATIONS	WEIGHT OF THE FOG MACHINE	ABOUT 46 KG
	WEIGHT WITH PACKAGING	ABOUT 49 KG
	UNITS ON ONE PALLET 100X120	24
	DIMENSION OF THE MACHINE	45,0X31,0XH45,0
	DIMENSION OF THE PACKAGING	61,0X49,0XH62,5
	COLORS	WHITE
	WORKING TIME WITHOUT MAINS POWER	ABOUT 5 HOURS
	HEAT UP TIME FROM COLD	ABOUT 8 HOURS
	VERTICAL OR CORNER MOUNTING	Yes
	HORIZONTAL MOUNTING	Yes
	SERIAL USB PORT FOR MONITORING	Yes
	NOZZLE TAMPER	Yes
	SERIAL BUS FOR STANDARD PROTOCOL	Yes
	ALARM KIT	OPTIONAL
FOG GENERATOR	NEW HEATING SYSTEM PLUS	Yes
	MAX FOG SINGLE SHOT 1,5 M VISIBILITY	Up to 6000 m ³
	MAX FOG SINGLE SHOT ZERO VISIBILITY	Up to 4000 m ³
	MAX SECONDS OF FOG EMISSION	2 mins.
	MAX FOG EMITTED WITH FULL FOG TANK	6000 m ³
	NUMBER OF CYLINDERS	1
	FOG TANK CAPACITY	1 x 4000 ml
	SHOOTING SPECIFICATION	Programmable in seconds
	CYLINDER/BAG MODEL	P4000
CYLINDER/BAG INCLUDED	1	
ELECTRICAL SPECIFICATIONS	POWER SUPPLY	220 V or 110 V
	AVERAGE POWER CONSUMPTION	80W
	BACK UP BATTERY	Yes
	PIR SENSOR VALIDATION INPUT	Yes
	SHOT CONFIRMATION OUTPUT	Yes
	POWER SUPPLY	Yes
	2AH BATTERY	Yes
STANDARDS	COMPLIES WITH EUROPEAN CE	Yes
	FOG FLUID IS CERTIFIED	Yes
	MEETS EUROPEAN STANDARD	Yes